

Description

Soft PVC film which conforms well with the substrate. Available in white and transparent. Matt surface.

Release paper

Silicone coated paper on one side, 125 g/m².

Adhesive

Polyacrylate, easily removable

Area of use

For short- and medium-term indoor applications such as markings, inscriptions and decorations.

Printing method

Screen printing is recommended. Special inks are necessary for UV-offset printing.

Technical data

Thickness* (without protective paper and adhesive)	80 micron
Dimensional stability (FINAT TM 14)	adhered to steel, no measurable shrinkage in cross direction, in length 0.4 mm max.
Adhesive power* (FINAT TM 1, after 24h, stainless steel)	3,5 N/25 mm
Tensile strength (DIN EN ISO 527)	
along	min. 19 MPa
across	min. 19 MPa
Elongation at break (DIN EN ISO 527)	
along	min. 130%
across	min. 150%
Shelf life**	2 years
Application temperature	> +10°C
Service life by specialist application (vertical application)	2 years

* average ** in original packaging, at 20°C and 50% relative humidity

Attention:

To not affect the adhesion surfaces to which the material is applied must be thoroughly cleaned from dust, grease or any contamination, they shouldn't be porous or structured. Coats of paint must be dry. The compatibility of selected lacquers and paints should be tested sby the user, prior to application of the material. Furthermore the application information for printing material published by ORAFOL is to be considered.

The batch traceability according to ISO 9001 is possible on the basis of the roll number.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.

